



CS

Dewaxing solvent for cotto, natural stone and concrete



DESTINATION → Terracotta, brick, natural stone and industrial cement floors. Do not apply on surfaces that are not resistant or sensitive to solvents.

PROPERTIES → **CS** is a product with an **energetic de-waxing action** based on **specific solvents and emulsifiers**, designed to address the problems of **removing various treatments** (acrylic or paste finishing waxes, waxy, acryl-wax or polymeric treatments), of uncertain nature and / or of particular resistance, not removable with **BASICO** or with standard alkaline detergents.

USE → Before any intervention **the flooring must be perfectly dry**. Apply the pure product with a brush or rag starting from the back wall of the room towards the door and **treating small surfaces at a time** (3-4 square meters). Allow the product to work **for about 10 minutes**, then brush the surface with an **abrasive pad** and / or a **single disc machine** with a brown or black abrasive disc, **wetting thoroughly with BASICO diluted in a 50% concentration in water** (see the technical data sheet). When the goal is achieved, **remove the residual solvent and resins using a wet vacuum cleaner** and / or absorbent paper, in order to prevent it from settling again. If further residues are present and evident, repeat the operations described above, otherwise **rinse thoroughly with clean water** and carry out the subsequent neutralization wash with **ACIDO** (see the technical data sheet). The success of the subsequent treatment is determined by a **perfect cleaning**, a **good rinse** as well as the **complete drying of the floor** (about 5-6 days). Establish through a preliminary test the resistance of the support to the product as well as the right application methodology to be used, in order to avoid possible undesired effects.

YIELD → As an indication only, **5-10 m²/l** of product.

TECHNICAL DATA

- **APPEARANCE:** transparent liquid
- **SPECIFIC WEIGHT:** 0,85 Kg/l ±0,1

PACKAGING

- 1CR203L1** → 12 x 1 liter plastic **BOTTLE**
- 1CR203L5** → 2 x 5 litres plastic **TANK**

SPECIFICATION → Dewaxing detergent with energetic action based on specific solvents and emulsifiers, specifically designed to address the problems of removing various treatments (acrylic or paste finishing treatments and waxes), of uncertain nature and / or of particular resistance from terracotta floors, bricks, natural stones and industrial cements (such as **CS** by CIR). It must be usable pure and in association with **BASICO** alkaline cleaner, it must be easily applied by brush or rag. The product in question must be accompanied by a 16-section safety sheet as required by the legislation in force.

WARNINGS

- Product intended for professional use.
- Carefully protect the surfaces to which the product is not intended.
- Do not apply in conditions of high humidity, imminent rain and in full sun conditions.
- Do not smoke or use naked flames during the application.
- Equip operators as required by current safety regulations.
- Properly ventilate enclosed spaces during use of the product.

All information contained in our records correspond to our best knowledge of current techniques and cannot be considered binding or challenging as the real application conditions, verifiable case, may also result in major changes of both practices described above and the results obtained. Perform preliminary tests to determine if the product is suitable for the intended or not. We decline any liability for any damage resulting from improper use or misuse of the product. Do not litter in the environment. This data sheet replaces all previous versions.