



# MUFFØUT PROTETTIVO

Product for the sanitation of painted surfaces, natural stone surfaces and artifacts in general



**F O C U S**  
professional and multifunctional products



**EDILIZIA**  
RISOLVERE PER MESTIERE



**DESTINATION** ➔ **Porous surfaces in general, painted and unpolished.** Always check the compatibility of the product with the support.

**PROPERTIES** ➔ Product in aqueous solution specific for the **sanification** of internal and external surfaces.

**MUFFØUT PROTETTIVO**, given its wide spectrum of action and its prolonged duration in time, is able to **limit the formation of stains and patinas due to the presence of pests**. Its selective action works without affecting or altering the support in any way. The product does not create films and is also applicable on painted substrates **without altering their color or appearance**. **MUFFØUT PROTETTIVO avoids the blackening of the internal walls** due to humidity and is ideal for application as a protective base on substrates to be painted.

**USE** ➔ On supports where there are already black spots and halos, it will be necessary to **proceed with a cleaning** of the surface with the specific product **MUFFØUT** or **MUFFØUT PROFUMATO**. Then apply **MUFFØUT PROTETTIVO** by **spraying it on the surface** to be protected from a distance of about 20 cm. Allow the product to absorb from the substrate without performing any further operation, simply removing any product dripping with a cloth or absorbent paper if they are not absorbed by the support. It is advisable to perform preliminary tests on the surfaces to be treated in order to avoid possible unwanted effects.

**YIELD** ➔ Approximately, **10-12 sqm. per bottle.**

## TECHNICAL DATA

- ➔ **APPEARANCE:** colorless transparent liquid
- ➔ **pH:** 3,5 ± 0,5
- ➔ **SPECIFIC WEIGHT:** 1 Kg/l ± 0,1

## PACKAGING

**1CR511L05** ➔ 12 x 500 ml plastic **SPRAY BOTTLE**

## WARNINGS

- ➔ Product intended for professional use.
- ➔ Operating temperatures: + 5 ° C / + 35 ° C.
- ➔ Do not apply in conditions of impending rain.
- ➔ Equip the operators as required by current safety regulations.
- ➔ Ventilate the closed rooms properly when using the product.

All information contained in our records correspond to our best knowledge of current techniques and cannot be considered binding or challenging as the real application conditions, verifiable case, may also result in major changes of both practices described above and the results obtained. Perform preliminary tests to determine if the product is suitable for the intended or not. We decline any liability for any damage resulting from improper use or misuse of the product. Do not litter in the environment. This data sheet replaces all previous versions.