

## TECHNICAL DATA SHEET

version 06/2024



# **IMPRESTONE TONO**

Wet-effect anti-stain impregnating treatment, solvent-based, for outdoor stone floorings









**DESTINATION** → Outdoor floorings in **absorbent natural stoned**.

PROPERTIES → IMPRESTONE TONO is a product based on particular fluoropolymers in solvent mixture, specific for water and oil-repellent protection of natural stone floorings. The water and oil-repellent characteristics prevent water (and the salts/pollutants dissolved in it), smog, dirt and greasy substances from penetrating the treated materials. It gives a pleasant "wet effect" to the treated surfaces, toning the natural color, while respecting the original aspect. Reduces the phenomenon of crumbling due to freezing and prevents the formation of salt efflorescences and moss and lichens which make the flooring slippery. The application of IMPRESTONE TONO does not involve changing the breathability of the support nor the decrease in its permeability to water vapour, it has a high resistance to UV rays.

USE → Apply the product only on absorbent, clean and dry surfaces. IMPRESTONE TONO it is ready to use and can be applied, as needed, with a soft brush made of natural fibers or a low-pressure sprayer, applying two successive coats, wet on wet, evenly and avoiding surface stagnation. In the case of particularly absorbent supports, apply until they are saturated. Wait for the floor to dry in order to evaluate the effectiveness of the treatment. Daily cleaning can be done using the specific PULI PAV product like a normal floor cleaner. Avoid caustic detergents, acids, ammonia or bleach. Carry out preliminary tests on the surface to be treated in order to avoid possible unwanted effects. After a few years, if necessary, it is possible to renew the treatment by applying, on a clean and dry surface, a further coat of IMPRESTONE TONO.

Solve any rising damp problems before carrying out the treatment wit IMPRESTONE TONO.

YIELD → As an indication 8-12 m²/l of product (complete treatment).

### **TECHNICAL DATA**

→ APPEARANCE: transparent liquid
→ SPECIFIC WEIGHT: 0,78 Kg/I±0,1

### **PACKAGING**

1CR304L1 → 6 x 1 liter plastic BOTTLE 1CR304L5 → 2 x 5 liters plastic TANK

SPECIFICATIONS → Product based on fluoropolymers in a solvent mixture specifically formulated for the water and oil-repellent treatment of natural stone floors placed outdoors (such as IMPRESTONE TONO by CIR). It must reduce the phenomenon of crumbling due to freezing temperatures and the formation of mosses and lichens which make the flooring slippery. It must promote the elimination of saltnitrate and prevent the penetration of dirt and air pollutants. It must make the materials resistant to greasy and oily stains, it must be breathable and it must give a "wet effect" to the treated surface. It must be easily applicable by brush or spray. It must be reversible. The product in question must be accompanied by a 16-section safety data sheet as required by current legislation.

#### **WARNINGS**

- Product intended for professional use.
- → Operating temperatures: +5°C/+35°C
- → Carefully protect surfaces for which the product is not intended.
- → Do not apply in conditions of high humidity, imminent rain or full sun.
- → Do not smoke during application.
- → Ventilate closed rooms adequately when using the product.
- → Equip operators as required by current safety regulations.

All information contained in our records correspond to our best knowledge of current techniques and cannot be considered binding or challenging as the real application conditions, verifiable case, may also result in major changes of both practices described above and the results obtained. Perform preliminary tests to determine if the product is suitable for the intended or not. We decline any liability for any damage resulting from improper use or misuse of the product. Do not litter in the environment. This data sheet replaces all previous versions.